



RESILIENT | ELITE XP

DESIGNED TO PERFORM
MADE TO EXCEL

PERFORMANCE DEFINED



TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.



ENERGY SAVING

Trelleborg is the **largest approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.



STABILITY

Trelleborg products are designed to have **large footprints** giving a maximum contact area leading to better stability and even tire wear.



COMFORT


Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

PERFORMANCE AGAINST PREMIUM COMPETITOR

TIRE LIFE



ENERGY SAVING



STABILITY



COMFORT



TRELLEBORG ELITE XP

Trelleborg Elite XP delivers everything that today's materials handling equipment requires – wear resistance, stability and driver comfort. Elite XP's unique design minimizes distortion increasing overall stiffness and confirms Elite XP as the tire of choice for the global materials handling industry. Elite XP's exceptional performance results from extensive R&D and testing processes, designed to create the tire that meets the ever increasing demands of industry today.



Elite XP

Tire Size	Rim	Profile	Tread Width (in)	Overall Diameter (in)	Load Capacity 10 mph (lbs)	Load Capacity 6 mph (lbs)	Weight (lbs)
3.00 x 4	2.10	XP	3.0	9.8	1,080	1,480	8.4
15 x 4.5 - 8	3.25	XP	4.6	14.9	1,570	2,170	22.5
15 x 4.5 - 8	3.00	XP	4.6	14.9	1,450	2,000	22.5
400 x 8	3.00	XP	4.1	16.0	1,685	-	25.1
16 x 6-8	4.33	XP	6.0	16.2	2,300	3,170	36.4
500 x 8	3.00	XP	4.8	18.0	1,930	2,670	38.4
500 x 8	3.75	XP	6.0	18.0	1,930	2,670	35.1
18 x 7-8	4.33	XP	6.2	18.0	2,700	3,750	47.9
140/55-9	4.00	XP	4.6	15.0	2,785	3,045	23.4
200/50-10	6.50	XP	7.8	18.0	3,770	5,200	55.8
600 x 9	4.00	XP	5.6	20.6	3,065	4,230	58.9
21 x 8-9	6.00	XP	7.3	20.3	4,480	6,190	74.3
650 x 10	5.00	XP	6.7	22.6	4,210	5,810	80.5
23 x 9-10	6.50	XP	7.9	23.0	5,450	7,525	106.1
23 x 10-12	8.00	XP	9.5	23.0	6,385	8,820	113.6
700 x 12	5.00	XP	6.7	25.6	4,810	6,640	105.4
27 x 10-12	8.00	XP	9.5	26.6	7,735	10,680	166.9
7.00-15	6.00	XP	6.3	28.7	6,250	8,620	105.4
700 x 15	5.50	XP	7.1	28.8	5,725	7,900	130.5
815 x 15 (28x9-15)	7.00	XP	8.9	27.3	6,520	9,000	139.6
750 x 15	6.50	XP	7.6	29.3	6,765	9,340	146.2
250 x 15	7.00	XP	8.9	28.0	6,960	9,615	149.5
250 x 15	7.50	XP	8.9	28.0	7,460	10,300	158.3
355/50-15 (28 x 12.5 - 15)	9.75	XP	11.2	28.0	9,250	12,760	194.5
825 x 15	6.50	XP	8.2	31.8	7,875	10,870	198.7
300 x 15	8.00	XP	10.0	32.0	9,554	13,190	240.8
355/65-15 (32x12.1-15)	9.75	XP	11.2	32.0	11,405	15,745	264.8
1000 x 20	7.50	XP	9.2	39.7	10,614	14,658	347.2
1000 x 20	8.00	XP	9.2	39.7	12,320	17,015	352.6
1200 x 20	8.00	XP	10.0	42.9	13,475	18,600	457.3
1200 x 20	8.50	XP	10.2	42.9	14,310	19,700	421.5
1200 x 20	10.00	XP	12.3	42.9	16,840	23,255	540.0
1200 x 24	8.50	XP	12.5	46.8	20,500	20,700	573.2
1200 x 24	8.50	HT	12.2	46.8	20,500	20,700	573.2
1200 x 24	10.00	XP	11.6	46.8	20,500	20,700	578.0
1400 x 24	10.00	HT	12.9	52.0	20,365	26,130	846.5
1400 x 24	10.00	XP	12.8	52.0	20,365	26,130	857.7
1600 x 25	11.25	XP	16.1	56.8	24,750	34,180	1,292.1

AVAILABLE ADDITIONAL COMPOUNDS



NON-MARKING

A high performance non-marking compound for use in applications where floor care is essential.

SPECIAL COMPOUNDS

Our compounding expertise allows us to offer a wide range of compounds. Please contact us for more details

